



1213 West Loop North, Ste 180
 Houston, TX 77055
 Phone: 713-688-2008
 Fax: 713-688-2993
 www.cccmix.com

AZ Inline Static Mixer Performance Chart

ALL 1.0" (25mm), 1.5" (38mm), 2.0" (50mm), and 3.0" (75mm) MODELS
 PERFORMANCE CHART

Head		Velocity of Discharge
PSI (BAR)	FEET (METERS)	FT/SEC (M/SEC)

10 (0.7)	23 (7.0)	39 (12.0)
20 (1.4)	46 (14.0)	55 (17.0)
30 (2.0)	69 (21.0)	67 (20.0)
40 (2.76)	92 (28.0)	77 (23.0)
50 (3.5)	115 (35.0)	86 (26.0)
60 (4.14)	138 (42.0)	94 (29.0)
70 (4.8)	161 (49.0)	102 (31.0)
80 (5.5)	184 (56.0)	109 (33.0)

AZ Mixing Element			
AZ-ISM-1 (1.0")	AZ-ISM-1.5 (1.5")	AZ-ISM-2 (2.0")	AZ-ISM-3 (3.0")
GPM (LPM)	GPM (LPM)	GPM (LPM)	GPM (LPM)

72 (274.0)	148 (562.0)	289 (1098.0)	714 (162.0)
102 (387.0)	209 (794.0)	408 (1550.0)	1009 (228.0)
125 (475.0)	256 (970.0)	500 (1900.0)	1325 (300.0)
145 (550.0)	296 (1124.0)	578 (2200.0)	1430 (324.0)
162 (615.0)	330 (1254.0)	647 (2458.0)	1595 (363.0)
177 (672.0)	362 (1375.0)	708 (2700.0)	1748 (397.0)
191 (725.0)	390 (1482.0)	765 (2900.0)	1890 (430.0)
205 (778.0)	418 (1588.0)	818 (3110.0)	2020 (459.0)

*Flow rates are based on water viscosity at 72° F (22° C).