

Chaos Mixer

Performance Chart

Insert nozzle orifice size to meet the application flow requirement motive pressure (PSI)

Dual Nozzle Size

PSI (BAR)	.75" (19.0mm)	1.0" (25.4mm)	1.5" (38.1mm)	2.0" (50.8mm)	2.5" (63.5mm)	3.0" (76.2mm)
	GPM (LPM)	GPM (LPM)	GPM (LPM)	GPM (LPM)	GPM (LPM)	GPM (LPM)
30 (2.0)	120 (456.0)	250 (950.0)	700 (2,649.8)	1,300 (4,921.0)	2,000 (7,570.8)	2,800 (10,599.1)
40 (2.76)	150 (570.0)	285 (1083.0)	850 (3,217.6)	1,415 (5,356.3)	2,200 (8,328.0)	3,100 (11,734.8)
50 (3.5)	165 (627.0)	310 (1178.0)	950 (3,596.1)	1,500 (5,678.1)	2,340 (8,857.9)	3,400 (12,870.4)
60 (4.14)	185 (703.0)	330 (1254.0)	1,025 (3,880.0)	1,700 (6,435.2)	2,600 (9,842.1)	3,800 (14,384.6)
70 (4.8)	200 (760.0)	358 (1360.0)	1,150 (4,353.2)	1,850 (7,003.0)	3,000 (11,356.2)	4,100 (15,520.2)
80 (5.5)	215 (817.0)	370 (1466.0)	1,225 (4,637.1)	2,000 (7,570.8)	3,200 (12,113.3)	4,800 (18,170.0)

*Mixing Chamber sized for each application

Compatible Components Corporation

Website: www.cccmix.com • Email: sales@cccmix.com

Telephone: 713-688-2008 • Fax: 713-688-2993

Address: 1234 North Post Oak Rd., Suite 100 Houston, TX 77055

